

Implementation of 16x16bit and 32x32bit Vedic Multiplier using FPGA board

^{#1}Ms. Ayushi Sharma, ^{#2}Mr. Ajit Singh

^{#1}M.Tech. Student, ^{#2}Assistant Professor And Faculty Guide, EC Department (VLSI DESIGN), A.P.J. ABDUL KALAM Technical University, Lucknow, Uttar Pradesh Ideal Institute Of Technology, Ghaziabad, Uttar Pradesh, INDIA

Abstract- This paper proposed the implementation of 16x16bit and 32x32bit Vedic Multiplier using modified Ripple Carry Adder, modified Kogge Stone Adder and BRENT KUNG ADDER on Spartan 6 family xc6slx4 -3-tgg144 FPGA and its synthesis using XILINX ISE 14.1 simulator and coding is done using VERILOG HDL. Vedic Mathematics is the ancient system of mathematics which has a unique technique of calculations based on 16 Sutras. The work has proved the efficiency of Urdhva Tiryakbhyam– Vedic method for multiplication which strikes a difference in the actual process of multiplication itself. It enables parallel generation of intermediate products, eliminates unwanted multiplication steps with zeros and scaled to higher bit levels using Karatsuba algorithm with the compatibility to different data types. Urdhva Tiryakbhyam Sutra is most efficient Sutra (Algorithm), giving minimum delay for multiplication of all types of numbers, either small or large.

Keywords- Kogge Stone Adder, Ripple Carry Adder, BRENT KUNG ADDER, FPGA board, Urdhva Tiryakbhyam, Verilog HDL.

I. INTRODUCTION TO FPGA

The Field Programmable Gate Array is also known as FPGA board. This is basically a board consisting of semiconductors engineered to remain programmable after production. Rather than locking in projects prior to manufacturing, engineers utilizing FPGA boards can test a wide range of different variables after building the entire board. In essence, the boards consist of hundreds or thousands of logic cells, and generally contain a number of inputs and outputs.

The FPGA board is a computing technology that has been in use nearly thirty years by engineering students and professionals alike. In design of an electronics project that requires computation and programming, the FPGA board is the best choice. The ease and flexibility afforded by the boards have made them incredibly popular. Fig.1 shows an FPGA board.



Fig.1 FPGA BOARD

II. DEVELOPMENT OF FPGA BOARDS

The first commercial FPGA boards were developed in the mid-1980s. This technology grew in popularity through the late 1990s. Today, the market for these boards is estimated at nearly \$3 billion. While the boards have used a number of different types of processing technologies in the past, today's FPGA boards predominantly utilize SRAM processing. Xilinx and Altera are the most prominent manufacturers of FPGA boards. Xilinx, which first developed the technology, remains the leader with 50% market share. Companies such as QuickLogic, SiliconBlue Technologies, Actel and Lattice Semiconductor also offer these products. Predefined circuits available from FPGA board manufacturers or from independent developers are often used to expedite the design of projects. Most vendors also provide software that engineers can use to design, run simulations and program the boards.

III. STEPS OF IMPLEMENTATION

Connect FPGA kit with the machine and select JTAG after connecting JTAG cable of FPGA kit with CPU and then follow the following steps:

Step1: Open the File. Go to Project Design Properties; change the Design properties as shown in an example in Fig.3, Family name as Spartan3, Device as XC3S200, Package as TQ144 and Speed as -4.




Fig.7



Fig.9



Fig.8

Step6: Now a message will appear in the message box as ‘Boundary scan-chain validated successfully’ and it started executing command as shown in Fig.9.

Step7: Now on the connected FPGA Spartan6 Development Kit provide the input with the switches according to provided Pin names in Step2. Here, in Fig.10 and Fig.11 Spartan 3 FPGA kit is shown just to make understand the implementation of a Vedic Multiplier on FPGA. A Spartan 3 can work only for 2x2bit and 4x4bit Vedic Multiplier as only 8 output providing LEDs are available with the Spartan3 kit.

Suppose for vedic multiplier 4x4bit, we have selected switch names for 4bit input A as P14 for A[0], P15 for A[1], P17 for A[2] and P18 for A[3] in which A[3] is LSB and A[0] is MSB. Select switch names for input B as P20 for B[0], P21 for B[1], P23 for B[2] and P24 for B[3] in which B[3] is LSB and B[0] is MSB. Suppose we are providing inputs for 4bit input A as 0011(i.e. 3 in Decimal) and for 4bit input B also as 0011(i.e. 3). Output multiplication of 3 with 3 must be 9(i.e. 00001001 in 8bit binary). For 8bit output we are providing pin names as P25, P26, P27, P28, P30, P31, P32, P33 in which P25 is for MSB and P33 is for LSB. LEDs glowing for output 9 is shown in Fig.10.

V. BENEFITS OF FPGA BOARD

1. The immediately obvious benefit of an FPGA board is the flexibility to quickly and easily configure programming in the course of development. These chips deliver better computing power than comparable alternatives, and are often more affordable.
2. It is more efficient to evaluate new product functionality and design using an FPGA board.
3. An FPGA board can perform both digital and analog functions, making it a versatile solution for engineers.
4. Some boards also support encryption to address security concerns raised by the essential flexibility of their architecture.

VI. APPLICATIONS

1. Due to the low cost and high performance, FPGA boards are now used for a wide variety of computing applications.
2. FPGA boards are also ideal for teaching electronics engineering and programming.
3. Amateur engineers can use an FPGA board to develop a variety of fun projects. These can include sound and music generators, LED displays and even games.
4. From the amateur hobbyist to the multinational corporation, tinkerers of all types are using the FPGA board to test new designs and ideas.
5. The field programmable gate array allows for rapid prototyping, testing and deployment. Many engineers today rely on FPGA board technology to explore innovative products.

VII. REFERENCES

1. Shilpi Thawait, Jagveer Verma, "FPGA Implementation of Simple and High Speed Vedic Multiplier", SSRG International Journal of VLSI & Signal Processing (SSRG-IJVSP), Volume 2, Issue 3, May-June 2015.
2. Gundlapalli Nandakishore, K.V. Rajendra Prasad, "FPGA Implementation of 8bit Vedic Multiplier by using Complex Numbers", Int. Journal of Engineering Research and Applications, Vol. 4, Issue 5(Version 6), June 2014.
3. Rupa A. Tomaskar, Gopichand D. Khandale,"FPGA Implementation of Complex Multiplier Using Urdhva Tiryakbhyam Sutra of Vedic Mathematics", International Journal of Engineering Research and Applications (IJERA), Vol. 4, Issue 5(Version 3), May 2014.
4. Mrs.Toni J.Billore, Prof.D.R.Rotake, "FPGA Implementation of High Speed 8bit Vedic Multiplier using Half Adders", IOSR Journal

- of VLSI and Signal Processing (IOSR-JVSP), Volume 4, Issue 3, Ver. II (May-Jun. 2014).
5. Sudeep.M.C., Sharath Bimba.M, Mahendra Vucha, "Design and FPGA Implementation of High Speed Vedic Multiplier", International Journal of Computer Application (IJCA), Volume 90, No.-16, March 2014.
6. Pavan Kumar U.C.S, Saiprasad Goud A, A.Radhika , "FPGA Implementation of High Speed 8bit Vedic Mulyiplier using Barrel Shifter", International Journal of Emerging Technology and Advanced Engineering (IJETAE), Volume 3, Issue 3, March 2013.
7. S R Panigrahi, O P Das, B B Tripathy, T K Dey , "FPGA Implementation of a 4x4 Vedic Multiplier", International Journal of Engineering Research and Development (IJER), Volume 7, Issue 1, May 2013.